Rockford Sanitary Systems, Inc. ROCKFORD, IL 61125-0963 (815) 229-5077 - (800) 747-5077 - FAX (815) 22

ROCKFORD, IL 61125-0963
(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108
WEB SITE-www.rkfdseparators.com E MAIL-rssem@rkfdseparators.com

MODEL NO. RP-25

GREASE INTERCEPTOR

DRAWN BY JOB NAME QUOTE # W.R.W. OPTIONAL FEATURES (ADDITIONAL COST) ☐ ANCHOR FLANGE EPOXY COATING □STAINLESS STEEL CONSTRUCTION ☐ INTEGRAL EXTENSION _____INCHES ☐ INLET & OUTLET SIZE ____INCHES DUTLET ALUMINUM COVER INLET ☐ THREADED CONNECTIONS 10.00 - 29,25 - - 26.00 - - 20.00 - 4.50 4.50 18.00 13.50 13.50 INLET DUTLET - 17,25 -

Specifications

Rockford Model RP-25 all welded steel interceptor, for on the floor or flush with the floor installation, 25 g.p.m. intermittent flow, 50 lbs. grease capacity, 3.00" no-hub inlet and outlet connections and flow control device, removable 3/16" nonskid diamond treadplate cover for on the floor or flush with floor installation suitable for pedestrian traffic, secured with stainless steel flat head screws, heavy duty leak-proof gasket, enamel coating inside and outside

Optional features (Additional cost) listed above



Approved By

Company

Date