Rockford Sanitary Systems, Inc.

ROCKFORD, IL 61125-0963

(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108
WEB SITE-www.rkfdseparators.com E MAIL-rssem@rkfdseparators.com

MODEL NO.

RTO - 35

GREASE SEPARATOR

DRAWN BY JOB NAME QUOTE # W.R.W. — Optional Outlet Location -|4.87|-NOTE: Inlet Outlet No Optional Features Available 10.50 -Optional Outlet Location 35,13 -- 21.00 -27,25 -5.87 6.00 10.50 27.00 23.75 21.00 16.50 Inlet Nutlet

Specifications

Rockford Model RTD-35 all welded steel separator, 40 gallon static capacity, 35 g.p.m. intermittent flow, 3.00" tapped inlet/outlet with 2.00" tapped internal vent connection, 120 lbs greasy sludge capacity, visible double-wall outside trap seal, separator plate and removeable filter screen, removable 3/16" nonskid diamond treadplate cover for flush with floor installation suitable for pedestrian traffic secured with stainless flat head screws, heavy duty leak-proof gasket, enamel coating inside and outside. Shipped withrequired outlet fittings, & (2) plugs for unused optional outlet locations.

Approved	Ву