

ROCKFORD SEPARATORS 5159 28th Ave ROCKFORD, IL 61109

5159 28th Ave ROCKFORD, IL 61109 (815) 229-5077 - FAX (815) 229-5108 www.rkfdseparators.com - rssem@rkfdseparators.com

MODEL NO. GF-23-LO-M			
GREASE SEPARATOR			
DRAWN BY R.P.P.			

QUOTE#:	DATE: 03/29/22	JOB NAME:
7.13		OPTIONAL FEATURES (ADDITIONAL COST) ANCHOR FLANGE CLAMP RING RECESSED LIFT HANDLES IN COVERS EPOXY COATING ANODES REINFORCED COVER STAINLESS STEEL CONSTRUCTION SEDIMENT BASKET FILTER MEDIA INTEGRAL EXTENSION INCHES ALTERNATE VENT TAPPING SIZE INCHES ALTERNATE INLET & OUTLET SIZE INCHES CAST IRON OUTLET FITTINGS PVC OUTLET FITTINGS
27.75 23.00 4.00 6.00 INLET		17.00 7.13 0UTLET

SPECIFICATIONS

Rockford Model GF-23-LO-M all welded 10 Ga. steel separator, 10 gallon static capacity, 16 g.p.m. intermittent flow, 2.00" tapped inlet and outlet connection, 65 lbs. greasy sludge capacity, visible double-wall outside trap seal, easily removable filter screen removable 3/8" nonskid diamond tread-plate cover for flush in the floor installation suitable for pedestrian traffic secured with stainless flat head screws, heavy duty leak-proof gasket, OPEX Shop Coat coating inside and bituminous coating outside.

Optional features (Additional cost) listed above

Optional reactives (Additional Cost) listed above		
Approved By	Company	Date