

Optional features (Additional cost) listed above

Approved By

ROCKFORD SEPARATORS 5159 28th Ave ROCKFORD, IL 61109

5159 28th Ave ROCKFORD, IL 61109 (815) 229-5077 - FAX (815) 229-5108 www.rkfdseparators.com - rssem@rkfdseparators.com

	MODEL NO. GF-50-LO-L		
	GREASE SEPARATOR		
	DRAWN BY R.P.P.		

Date

QUOTE#:	DATE: 03/29/22	JOB NAME:			
INLET III	OUTLET		OPTIONAL FEATURES (ADDITIONAL COST) ANCHOR FLANGE CLAMP RING RECESSED LIFT HANDLES IN COVERS EPOXY COATING ANODES REINFORCED COVER STAINLESS STEEL CONSTRUCTION SEDIMENT BASKET FILTER MEDIA INTEGRAL EXTENSION INCHES ALTERNATE VENT TAPPING SIZE INCHES ALTERNATE INLET & OUTLET SIZE INCHES CAST IRON OUTLET FITTINGS PVC OUTLET FITTINGS		
52.25 34.50 9.25 INLET	VENT	16,00	29.56 23.00 5.00 11.00 OUTLET		
49.50		-	20.25		
SPECIFICATIONS Rockford Model GF-50-LO-L all welded 10 Ga. steel separator, 41 gallon static capacity, 41 g.p.m. intermittent flow, 3.00" tapped inlet/outlet with 2.00" tapped internal vent connection, 250 lbs greasy sludge capacity, visible double-wall outside trap seal, easily removable separator screen and filter screen, removable 3/8" nonskid diamond tread plate cover for flush with floor installation suitable for pedestrian traffic secured with stainless flat head screws, heavy duty leak-proof gasket, OPEX Shop Coat coating inside and bituminous coating outside.					

Company