Rockford Sanitary Systems, Inc. ROCKFORD, IL 61125-0963

(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108 WEB SITE-www.rkfdseparators.com E MAIL-rssem@rkfdseparators.com

MODEL NO.

GOST-5648-300

DIL/SAND SEPARATOR

DRAWN BY JOB NAME QUOTE # W.R.W. OPTIONAL FEATURES (ADDITIONAL COST) **VENT** ☐ ANCHOR FLANGE ☐ FILTER MEDIUM RECESSED LIFT HANDLES IN COVERS 33.00 □EPOXY COATING ┌─ ANODES REINFORCED COVERS LOAD 11.38 11.38 ISTAINLESS STEEL CONSTRUCTION **VENT** ⊐SEDIMENT BASKET ☐ INTEGRAL EXTENSION _ ☐ INLET & DUTLET SIZE _____ INCHES ☐ DOUBLE WALL CONSTRUCTION INLET ☐ LEAK DETECTION □HIGH LEVEL SENSOR & ALARM COALESCING PACK \odot DUTLET 45.63 **VENT** 11.38 11.38 33.00 **VENT** 99.18 - 91,25 -85.63 -30,38 **VENT** 17,50 0 0 0 22.00 48.00 38.00 30,50 26,00 **INLET** DUTLET

Specifications

Rockford model GDST-5648-300 oil/water separator all welded A36 .25" steel, 200 gpm intermittent flow, 285 gallon static capacity with 300 gallon waste oil storage and an additional 230 gallon sediment chamber, 4" threaded in/out and 4" threaded vent connections, visible double wall outside trap seal, removable filter screen, non removable separator baffles, 37" nonskid treadplate covers for flush with floor installation suitable for pedestrian traffic secured with stainless steel bolts, heavy duty gasket, opex shop coating inside and bituminous coating outside.

Optional features (Additional cost) listed above

Approved By	Company	Date