



Rockford Sanitary Systems, Inc.

ROCKFORD, IL 61125-0963

(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108

WEB SITE-www.rkfdseparators.com E MAIL-rssem@rkfdseparators.com

MODEL NO.

GSS-18

SAND SEPARATOR

DRAWN BY

QUOTE #


JOB NAME

W.R.W.

OPTIONAL FEATURES (ADDITIONAL COST)



- ANCHOR FLANGE
- RECESSED LIFT HANDLES ___ PER COVER
- EPOXY COATING
- LIGHT TRAFFIC REINFORCED COVERS
- HEAVY TRAFFIC REINFORCED COVERS
- STAINLESS STEEL CONSTRUCTION
- SEDIMENT BASKET
- INTEGRAL EXTENSION _____ INCHES
- INLET & OUTLET SIZE _____ INCHES
- DOUBLE WALL CONSTRUCTION
- LEAK DETECTION
- FILTER MEDIUM
- ANODES
- HOLD DOWN PADS
- ALUMINUM COVER
- NO HUB CONNECTION
- HUB CONNECTION

Vent
4 Places



Outlet

Inlet



Specifications

Rockford Model GSS-18 Gravel & Sand Separator all welded A36 1/4" steel, 405 gallon static capacity (54 Cubic feet), 4.00" Threaded inlet and outlet, 2.00" threaded vent connections (4), removable filter screen, non-removable baffle plates, (2) 3/8" nonskid diamond treadplate cover (for flush-with-floor installation) for pedestrian traffic, secured with stainless steel flat head screws, heavy duty leakproof gasket, OPEX SHOP COAT coating inside & bituminous coating outside.

Optional features (Additional cost) listed above

Approved By

Company

Date