INLET

Rockford Sanitary Systems, Inc. ROCKFORD, IL 61125-0963

MODEL NO. OSTL-5648-300

(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108 WEB SITE-www.rkfdseparators.com E MAIL-rssem@rkfdseparators.com DIL/WATER SEPARATOR DRAWN BY JOB NAME QUOTE # W.R.W. OPTIONAL FEATURES (ADDITIONAL COST) VENT ☐ ANCHOR FLANGE ☐ FILTER MEDIUM RECESSED LIFT HANDLES IN COVERS - 11.38 □EPOXY COATING ┌─ ANODES REINFORCED COVERS LOAD 11.38 ISTAINLESS STEEL CONSTRUCTION **VENT** ⊐SEDIMENT BASKET ☐ INTEGRAL EXTENSION _ ☐ INLET & DUTLET SIZE _____INCHES ☐ DOUBLE WALL CONSTRUCTION ☐ LEAK DETECTION □ HIGH LEVEL SENSOR & ALARM COALESCING PACK DUTLET INLET VENT 20.00 11.38 - 11.38 VENT 77.75 - 91,25 -64.25 -30,38 **VENT** 17.50 0 0 0 22.00 48.00 38.00 30.50 26.00

Specifications

DUTLET

Rockford Model OSTL-5648-300 Dil/Water Separator all welded A36 10ga. steel, 200 g.p.m. intermittent flow, 285 gallon static capacity with 300 gallon waste oil storage, 4.00" threaded inlet/outlet & 4.00" threaded vent connections (4), visible double-wall outside trap seal, removable filter screen, non-removable separator screens, 3/16" nonskid treadplate covers (6) (for flush-with-floor installation) for pedestrian traffic secured with stainless steel bolts with heavy duty leakproof gasket, OPEX SHOP COAT coating inside & bituminous coating outside.

Untional features (Additional cost) listed above

Lip vioriat i ca vai es	TIGGINOTIAL COS UN TIS VEGI ANOVE		
Approved By	Company	Date	