

## ROCKFORD SEPARATORS 5159 28th Ave ROCKFORD, IL 61109

(815) 229-5077 - FAX (815) 229-5108 www.rkfdseparators.com - rssem@rkfdseparators.com **MODEL NO. RP-250 GREASE INTERCEPTOR** 

DRAWN BY R.P.P.

QUOTE#: **DATE: 03/08/24 JOB NAME:** OPTIONAL FEATURES (ADDITIONAL COST) ANCHOR FLANGE ☐ EPOXY COATING ☐ STAINLESS STEEL CONSTRUCTION INTEGRAL EXTENSION \_ **INCHES** INLET & OUTLET SIZE \_ INCHES ALUMINUM COVER THREADED CONNECTIONS OUTLET INLET 19,63 64.25 61.00 9.00 OUTLET 19.63 19.63 53.00 54,00 54,00 INLET OUTLET 58.25 39.25

## **SPECIFICATIONS**

Rockford Model RP-250 all welded steel interceptor, with 509 gallon static holding capacity and 250 g.p.m. intermittent flow, 500 lbs. grease capacity, 4.00" no-hub inlet and outlet connections and flow control device, removable 3/16" nonskid diamond tread-plate cover for on the floor or flush with floor installation suitable for pedestrian traffic, secured with stainless steel flat head screws, heavy duty leak-proof gasket, enamel coating inside and outside

Optional features (Additional cost) listed above		
Approved By	Company	Date