Rockford Sanitary Systems, Inc. ROCKFORD, IL 61125-0963

(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108 WEB SITE-www.rkfdseparators.com E MAIL-rssem@rkfdseparators.com

MODEL NO. RTO - 50 - 10

GREASE SEPARATOR

DRAWN BY JOB NAME QUOTE # W.R.W. 11.38 Optional Outlet Location NOTE: No Optional Inlet □utlet Features Available 10,50 Optional Outlet Location 11.38 58,88 -23,00 52.25 -6.38 5.00 9.25 16.00 12.50 11,00 6.75 Dutlet Inlet

Specifications

Rockford Model RTD-50-LD all welded steel separator, 41 gallon static capacity, 50 g.p.m. intermittent flow, 3.00" tapped inlet/outlet with 2.00" tapped internal vent connection, 250 lbs greasy sludge capacity, visible double-wall outside trap seal, separator plate and removeable filter screen, removable 3/16" nonskid diamond treadplate cover for flush with floor installation suitable for pedestrian traffic secured with stainless flat head screws, heavy duty leak-proof gasket, enamel coating inside and outside. Shipped withrequired outlet fittings, & (2) plugs for unused optional outlet locations.

Approved By

Company

Date